



## HP LaserJet 1010/1012/1015 printer

			
<b>product models</b>	<b>q2460a</b>	<b>q2461a</b>	<b>q2462a</b>
<b>price list (GBP)</b>	<b>128.00</b>	<b>160.00</b>	<b>193.00</b>
<b>media handling/input</b>			
<b>tray 1 capacity</b>	up to 150 sheets, 10 envelopes		
<b>tray 1 weight</b>	60 g/m <sup>2</sup> to 105 g/m <sup>2</sup>		
<b>tray 1 size</b>	A4, A5, Letter, Legal, Executive, B5 (JIS), B5 (ISO), C5, DL, Monarch, Com-10, 76 x 127 mm to 216 x 356 mm		
<b>media handling/output</b>			
<b>sheets</b>	Up to 125		
<b>envelopes</b>	15		
<b>transparencies</b>	10		
<b>media handling</b>			
<b>standard media sizes</b>	A4, A5, Letter, Legal, Executive, B5 (JIS), B5 (ISO), C5, DL, Monarch, Com-10		
<b>media types</b>	Plain paper, envelopes, transparencies, cardstock, postcards, labels		
<b>max. media weight range</b>	Output bin: 60 to 105 g/m <sup>2</sup> , straight through paper media path: 60 to 163 g/m <sup>2</sup>		
<b>processor</b>			
<b>processor</b>	RISC processor		
<b>processor speed</b>	133 MHz		
<b>os compatibility</b>			
<b>os supported</b>	Microsoft® Windows® 98, Me, 2000, XP; Microsoft Windows XP 32-bit	Microsoft® Windows® 98, Me, 2000, XP; Windows 95, NT 4.0 (SP3); Microsoft Windows XP 32-bit (print driver only); Mac OS 9. v 9.1 and higher, Mac OS X v 10.1, 10.2; MS-DOS	
<b>os driver update</b>	Latest drivers available from <a href="http://www.hp.com">http://www.hp.com</a>		
<b>network os supported</b>	N/A	With optional HP Jetdirect 175x network print server: Microsoft® Windows® 98, Me, NT 4.0, 2000, XP, XP 64 bit, Apple Mac OS 8.6 and later; with optional HP Jetdirect 310x network print server or HP Jetdirect 380x 802.11b network print server: Microsoft Windows 98, Me, NT 4.0, 2000, XP, XP 64 bit, Apple Mac OS 8.6 and later, Novell™ NetWare 3.2, 4.2, 5.x, 6, Red Hat Linux 6.x and later, SuSE Linux 6.x and later, HP-UX 10.20, 11.x, Solaris™ 2.5x, 2.6, 7, 8 (SPARC systems only), IBM® AIX 3.2.5 and later (requires software from the NOS vendor), MPE-iX; for more information, refer to <a href="http://www.hp.com/support/net_printing">http://www.hp.com/support/net_printing</a>	
<b>system requirements</b>			
<b>minimum system requirements</b>	Operating system requirements as recommended by the operating system vendor plus free hard disk space (140 MB for full installation, 10 MB for print drivers only); CD-ROM disk drive; USB, dedicated IEEE-1284 compliant bi-directional parallel, or ECP-compliant parallel port		
<b>minimum for macintosh</b>	Power PC G3 or higher, OS 9.X: 64 MB RAM, OS X: 128 MB RAM, 15 MB free hard disk space, CD-ROM drive		
<b>memory</b>			

<b>standard</b>	8 MB	16 MB
<b>upgrade</b>	Not expandable	
<b>technology</b>	HP Resolution Enhancement REt and FastRes	
<b>maximum</b>	8 MB	16 MB
<b>interface and connectivity</b>		
<b>standard</b>	USB compatible with the USB 2.0 specification	Two hot ports: USB compatible with the USB 2.0 specification, IEEE 1284-compliant bi-directional parallel
<b>optional</b>	N/A	HP Jetdirect external print servers for Fast Ethernet (10/100Base-TX), Ethernet (10Base-T), Token Ring; HP wireless print servers for 802.11b Ethernet
<b>software included</b>	HP printer software on CD-ROM includes HP installer/uninstaller, host-based driver, HP toolbox for diagnostic status and configuration, help, documentation	HP printer software on CD-ROM includes HP installer/uninstaller, HP PCL 5e and host-based drivers, HP toolbox for diagnostic status and configuration, help, documentation
<b>control panel</b>	Simplified control panel with "Go" and "Cancel job" buttons, and three LEDs for status	
<b>physical dimensions</b>		
<b>dimensions (w x d x h) out of package</b>	370 x 230 x 208 mm	
<b>dimensions (w x d x h) package</b>	500 x 300 x 345 mm	
<b>weight out of package</b>	5.9 kg	
<b>weight package</b>	7.41 kg	
<b>power</b>		
<b>power requirements</b>	110 to 127 VAC (+/-10%), 50/60 Hz (+/-2 Hz); 220 to 240 VAC (+/-10%), 50/60 Hz (+/-2 Hz)	
<b>power supply type</b>	Built-in power supply	
<b>power consumption</b>	0 watts maximum (off), 7 watts maximum (Powersave/standby), 214 watts maximum (printing)	
<b>environmental ranges</b>		
<b>operating temperature</b>	10 to 32.5° C	
<b>operating humidity</b>	20 to 80% RH	
<b>recommended operating humidity</b>	20 to 80% RH	
<b>recommended operating temperature</b>	10 to 32.5° C	
<b>storage temperature</b>	0 to 40° C	
<b>storage humidity</b>	10 to 80% RH	
<b>noise level per iso 9296</b>		
<b>sound power</b>	6.2 B(A) (printing at 12 ppm)	6.2 B(A) (printing at 14 ppm)
<b>sound pressure</b>	57 dB(A) - operator position, 48 dB(A) - bystander	
<b>operating position lpam</b>	57 dB(A) - operator position, 48 dB(A) - bystander	
<b>additional information</b>		
<b>energy star</b>	Yes	