






## hp LaserJet 2300 series

					
<b>product models</b>	<b>q2472a</b>	<b>q2474a</b>	<b>q2473a</b>	<b>q2475a</b>	<b>q2476a</b>
<b>price list (GBP)</b>	<b>479.00</b>	<b>557.00</b>	<b>721.00</b>	<b>787.00</b>	<b>950.00</b>
<b>media handling/input</b>					
<b>tray 1 capacity</b>	100 sheets, 10 envelopes				
<b>tray 1 weight</b>	60 to 163 g/m2				
<b>tray 1 size</b>	envelopes, labels, transperencies, special media, 76 x 127 mm to legal size				
<b>tray 2 capacity</b>	250 sheets				
<b>tray 2 weight</b>	60 to 105 g/m2				
<b>tray 2 size</b>	A4, A5, letter, executive, legal, B5 (ISO), B5 (JIS) and custom sizes				
<b>tray 3 capacity</b>	500 sheets				
<b>tray 3 weight</b>	60 to 105 g/m2				
<b>tray 3 size</b>	A4 and letter				
<b>duplex size</b>	A4, letter, legal and custom sizes				
<b>media handling/output</b>					
<b>sheets</b>	250				
<b>media handling</b>					
<b>media types</b>	Paper (plain, letterhead, prepunched, bond, colour, rough, preprinted, recycled), envelopes, labels, postcards, cardstock (heavy paper)				
<b>processor</b>					
<b>processor</b>	RISC				
<b>processor speed</b>	266 MHz				
<b>os compatibility</b>					
<b>os supported</b>	Microsoft® Windows® (95, 98, NT 4.0, Me, 2000, XP), Apple® Mac® OS (8.6 to 9.xx, 10.1 (drivers not included, download at <a href="http://www.hp.com/support/lj2300">http://www.hp.com/support/lj2300</a> ); printing from DOS-based possible in compatibility mode. UNIX®/Linux: supported via HP Jetdirect (e.g. HP Web Jetadrn also <a href="http://linux.hp.com">http://linux.hp.com</a> )				
<b>os driver update</b>	Latest HP print drivers are available from <a href="http://www.hp.com/support/lj2300">http://www.hp.com/support/lj2300</a> , OS/2 drivers are and are packaged with OS/2.				
<b>os drivers included</b>	Drivers included: Microsoft® Windows® (95, 98, Me, NT 4.0, 2000, XP), Mac® OS (8.6 and downloadable: OS/2, UNIX, Linux. Download available at <a href="http://www.hp.com/support">http://www.hp.com/support</a>				
<b>network os supported</b>	Microsoft® Windows® 98, NT 4.0, Me, 2000, XP, XP 64-bit; Novell™ NetWare 3.2, 4.2, 5.x, 6; 8.6 and later; Red Hat Linux 6.x and later; SuSE Linux 6.x and later; HP-UX 10.20, 11.x; Solaris 8 (SPARC systems only); IBM® AIX 3.2.5 and later (requires software from the NOS vendor)				
<b>system requirements</b>					
<b>minimum system requirements</b>	Microsoft® Windows® 95 (basic functions only), 98: Pentium® 90 with 16 MB RAM; Windows with 32 MB RAM; Windows NT 4.0: Pentium 90 with 32 MB RAM; Windows 2000: 133 MHz processor with 32 MB RAM; Windows XP: 233 MHz processor with 64 MB RAM, 180 MB free hard disk space, CD-ROM or IEEE 1284-B compliant bi-directional parallel port.				
<b>minimum for macintosh</b>	Mac® OS 8.6 (basic functions only), Mac OS 9.x, and Mac OS X v10.1 and later, 160 MB free CD-ROM drive, USB port or IEEE 1284-B compliant bi-directional parallel port				
<b>memory</b>					
<b>standard</b>	32 MB	48 MB			
<b>upgrade</b>	Expandable to 288 MB through two industry-	Expandable to 304 MB through two industry-standard DIMM slots			

	standard DIMM slots	
<b>memory slots</b>	3 industry-standard DIMM slots	
<b>technology</b>	Memory Enhancement technology (MEt)	
<b>maximum</b>	288 MB	304 MB
<b>interface and connectivity</b>		
<b>standard</b>	1 bi-directional parallel port (IEEE 1284 ECP-compliant, B-size), 1 USB port (1.1 and 2.0 compliant), 1 open EIO slot	1 bi-directional parallel port (IEEE 1284 ECP-compliant, B-size), 1 USB port (1.1 and 2.0 compliant), Fast Ethernet 10/100Base-TX internal EIO print server
<b>optional</b>	HP Jetdirect (EIO) internal print servers; connectivity card for USB, serial and LocalTalk, 80 internal print server	
<b>software included</b>	Installer/Uninstaller; Windows 95, 98, Me, NT 4.0, 2000, and XP drivers (HP PCL 6, HP PCL Level 3 emulation); Macintosh software: PostScript Printer Description (PPD) files, Printer Driver (PDEs), and the HP LaserJet Utility; Screen fonts; Customization Utility; Printer Status and	
<b>control panel</b>	2-line graphical display with backlight; "?" (Help) button; "Back" button; "Pause/Resume" button; "Down Arrow" button; "Select" button; "Cancel Job" button; Ready, Data, and Attention	
<b>physical dimensions</b>		
<b>dimensions (w x d x h) out of package</b>	412 x 450 x 260 mm	413 x 450 x 397 mm
<b>dimensions (w x d x h) package</b>	500 x 600 x 358 mm	500 x 600 x 588 mm
<b>weight out of package</b>	14.3 kg	18.9 kg
<b>weight package</b>	16.75 kg	22 kg
<b>power</b>		
<b>power requirements</b>	110-volt models: 110 to 127 VAC (+/- 10%); 50/60 Hz (+/- 3 Hz); 220-volt models: 220 to 240 VAC (+/- 10%); 50/60 Hz (+/- 3 Hz)	
<b>power consumption</b>	426 watts maximum (printing), 9.6 watts maximum (standby), 9.3 watts maximum (powersave)	
<b>environmental ranges</b>		
<b>operating temperature</b>	15 to 32.5° C	
<b>operating humidity</b>	10 to 80% RH (no condensation)	
<b>recommended operating humidity</b>	10 to 80% RH	
<b>recommended operating temperature</b>	15 to 32.5° C	
<b>storage temperature</b>	-20 to 40° C	
<b>storage humidity</b>	10 to 90% RH	
<b>additional information</b>		
<b>energy star</b>	Yes	
<b>certifications</b>	Australia (C Tick-AS/NZS 3548), Canada (Industry Canada ICES 003-CISPR 22), China (CIS Directive 89/336/EEC), ISE Countries (CISPR 22), Japan (VCCI-B), Korea (MIC number 1996 Mark-CISPR 22), Russia (GOST-CISPR 22), Taiwan (BSMI Cert.-CNS 13438), USA (FCC Title Class B). CISPR22 to Class B	
<b>regulatory standards</b>	Czech Republic (CSN-IEC 60950-IEC 60825-1), Estonia (EEI-EN 60950-IEC 60825-1), EU (CE Directive 73/23/EEC), Germany (TÜV- EN 60950-IEC 60825-1), Hungary (MEEI- IEC 60950 Lithuania (LS- IEC 60950-IEC 60825-1), Poland (B Mark- IEC 60950-IEC60825-1), (Russia (Slovakia (IEC 60950-IEC60825-1), Slovenia (SQI- IEC 60950-EN 60825-1), South Africa (IEC 60950-1). Class 1 Laser/LED Product	
<b>vs</b>	CE marking for EU & EFTA countries (Low Voltage Directive 73/23/EEC & EMC Directive 89/336/EEC) Laser/LED (further details, see Declaration of Conformity) Further compliance is given for: US/Canada (UL/ETL), Russia GOST, Poland B-Mark, Czech Republic (CSN *), Estonia (EEI *), Hungary (MEEI *), Lithuania (LS *), Slovakia (STN *), Slovenia (SQI *), South Africa (SASB *) and more. (* = IEC 60950, IEC 60825-1 certificates: TÜV-GS approved, EPA ENERGY STAR compliant	